



100mm Bottom Entry SS **Case Overview**

Features

- Suitable for hydraulic oil and gaseous media that do not corrode any copper base alloy
- Available in nominal sizes 63 and 100
- Thread form: BSP (G1/4 and G1/2), NPT (1/4NPT and 1/2NPT)
- Housing made of Stainless Steel (1.4301)
- Sight glass made of Acrylic
- Glycerine filled
- U-bolt or flange mounting kit on request

Pressure Range	Units (secondary units)	Fitting	Fitting Material
0 to 6	Bar (PSI)	1/2" BSPP	Brass
0 to 10	Bar (PSI)	1/2" BSPP	Brass
0 to 16	Bar (PSI)	1/2" BSPP	Brass
0 to 25	Bar (PSI)	1/2" BSPP	Brass
0 to 40	Bar (PSI)	1/2" BSPP	Brass
0 to 60	Bar (PSI)	1/2" BSPP	Brass
0 to 100	Bar (PSI)	1/2" BSPP	Brass
0 to 160	Bar (PSI)	1/2" BSPP	Brass
0 to 250	Bar (PSI)	1/2" BSPP	Brass
0 to 315	Bar (PSI)	1/2" BSPP	Brass
0 to 400	Bar (PSI)	1/2" BSPP	Brass
0 to 600	Bar (PSI)	1/2" BSPP	Brass
0 to 680	Bar (PSI)	1/2" BSPP	Brass
0 to 700	Bar (PSI)	1/2" BSPP	Brass
0 to 100	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 160	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 250	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 400	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 600	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 800	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 1000	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 1600	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 2500	kPa (PSI)	1/2" NPT	Stainless Steel

Pressure Range	Units (secondary units)	Fitting	Fitting Material
0 to 4000	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 6000	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 10000	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 16000	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 25000	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 40000	kPa (PSI)	1/2" NPT	Stainless Steel
0 to 60000	kPa (PSI)	1/2" NPT	Stainless Steel